AMPHENOL CANADA
RACK & PANEL CONNECTORS

R39 FAMILY



- Unique proprietary rectangular product which uses the same contacts as standard *D38999* (*AS39029*)
- Low profile, blind mating, and rugged
- High density 127 position inserts or mixed inserts with power, RF or fiber optic available
- Both plug and receptacle configurations can be selected with either pin or socket contacts to allow maximum versatility

R39 - P 098 P T A 1 - 000

CONNECTOR SERIES

SHELL STYLE
P = Plug
R = Receptacle

INSERT PATTERN (N° OF CONTACTS)

017	056	127
031	098	

Filtered R39 configurations available
Consult factory

CONTACT GENDER
P = Pin
S = Socket

DEVIATION CODE


SHELL FINISH
1 = Electroless Nickel
2 = OD Chromate
3 = Tin
4 = Gold

MOUNTING TYPE
A = Standard Mount
B = Float

CONTACT TERMINATION
T = Crimp
B = PCB
C = Compliant

IMPROVED AND UPDATED

Download 2D drawings & 3D models using our online configurator



R398 SERIES
Harsh Environment



- Compact scoop-proof design for space efficiency and protection.
- Serves as a D-sub alternative with size 23 contacts.
- Offers available PCB and crimp terminations for flexibility.
- Ideal for applications requiring a smaller footprint and reliable connections.

R393 SERIES
High Speed



- Rugged multiport design for durability in challenging environments.
- Supports multiple RF contact styles, including shielded quadrax.
- Ensures reliable high-speed communications.
- Ideal for mission-critical applications.

Amphenol CANADA
MILITARY & AEROSPACE

www.amphenolcanada.com
5950 14th Avenue
Markham, ON
Canada, L3S 4M4

CONTACT OUR TEAM

FOR GENERAL ENQUIRIES

sales@amphenol-acc.com
+1 (416) 291-4401

FOR SALES SUPPORT BY REGION

Check:
amphenolcanada.com/**SalesLocations**